

# SAFETY DATA SHEET

**MOL-LUB Ltd.**

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: **MOL Hykomol LS 85W-90 limited slip gear oil**

Version: 2

Latest revision: 26. 08. 2013

Date of issue: 20. 06. 2007

Page: 1/(12)

## 1. Identification of the mixture and of the company/undertaking

### 1.1 Product identifier:

**MOL Hykomol LS 85W-90 limited slip gear oil**

### 1.2 Relevant identified uses of the mixture and uses advised against

Relevant identified uses: gear oil

Uses advised against: no data

### 1.3 Details of the supplier of the safety data sheet:

MOL-LUB Lubricant Production Trade and Service Limited Liability Company

H-2931 Almásfüzitő, Fő út 21., Hungary

Phone / Fax: +36 34 526 330 / +36 34 526 391

Request SDS of:

MOL-LUB Lubricant Production Trade and Service Limited Liability Company

Customer Service Center

H-2931 Almásfüzitő, Fő út 21., Hungary

Phone / Fax: +36 80 201 296 / +36 34 348 010

Responsible for SDS:

MOL-LUB Ltd. Csaba Horváth, head of SD and HSE

Phone: +36 34 526 343; Mobile: +36 20 474 2644

e-mail: csahorvath@mol.hu

Technical information:

MOL-LUB Ltd. Product Development and Technical Service

H-1117 Budapest, Október huszonharmadika utca 18., Hungary

Phone/Fax: +36 80 201 296 or +36 1 464 0236 / +36 1 464 0304

### 1.4 Emergency telephone number

Emergency telephone (07-15<sup>20</sup> h): +36 34 526 210 (CET) on workdays

Health Toxicological Information Service (ETTSZ 1096 Budapest, Nagyvárad tér 2.)

Tel.: +36 1 476 6464, or +36 80 201 199

National Health Toxicological Information Service:

## 2. Hazards identification

### 2.1 Classification of the mixture

#### 2.1.1 Classification of the mixture according to regulation 1272/2008/EC

Hazard Class and Category:

Hazard statement:

Eye Irrit. 2

H319

Causes serious eye irritation.

Skin Sens. 1

H317

May cause an allergic skin reaction.

# SAFETY DATA SHEET

MOL-LUB Ltd.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: **MOL Hykomol LS 85W-90 limited slip gear oil**

Version: 2

Latest revision: 26. 08. 2013

Date of issue: 20. 06. 2007

Page: 2/(12)

## 2.1.2 Classification of the mixture according to regulation 1999/45/EC

Human health hazards:	Xi (irritant)
R 43	May cause sensitisation by skin contact.
Note:	Prolonged and/or repeated contact may cause irritation on skin or in eyes depending on individual sensitivity (See also Protective equipment).
Safety hazards:	Danger symbol not required.
Environmental hazards:	Danger symbol not required.
Note:	Spills may form a film on water surfaces causing impaired oxygen transfer.

## 2.2 Label elements 1272/2008/EC

Product identification: Trade name: **MOL Hykomol LS 85W-90 limited slip gear oil**

Hazardous component: Reaction products of bis(4- methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14 alkyl(branched) (EU: 931-384-6)

GHS Pictogram:



Signal word: **Warning**

Hazard statement:

**H319** Causes serious eye irritation.  
**H317** May cause an allergic skin reaction.

Supplemental hazard information:

**EUH208** Contains Oleilamin and Formaldehyde, reaction products with branched and linear heptylphenol, carbon disulfide and hydrazine. May produce an allergic reaction.

Precautionary statements – Prevention:

**P280** Wear protective gloves/protective clothing/eye protection/face protection.  
**P273** Avoid release to the environment.

# SAFETY DATA SHEET

MOL-LUB Ltd.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: **MOL Hykomol LS 85W-90 limited slip gear oil**

Version: 2

Latest revision: 26. 08. 2013

Date of issue: 20. 06. 2007

Page: 3/(12)

Precautionary statements – Response:

**P333+P313**

If skin irritation or rash occurs: Get medical advice/attention.

**P337+P313**

If eye irritation persists: Get medical advice/attention.

**P363**

Wash contaminated clothing before reuse.

Precautionary statements – Disposal:

**P501**

Dispose of contents/container in accordance with national regulation.

Other liabilities for labelling:

Tactile warning of danger: Not required.

Transport classification: see section 14.


- 2.3 Other hazards  
no data available

## 3. Composition/information on ingredients

### 3.1 Mixtures

Chemical description: Mixture of refined mineral base oils containing additives.

Component(s) / Hazardous component(s):

Name	EINECS number	CAS number	Hazard symbol / Hazard classes and cat.	Risk phrase / Hazard statements	Conc. % (m/m)
Lubricating oils (petroleum), C>25* REACH Registr.Nr.: 01-2119486948-13	309-874-0	101316-69-2	67/548/EEC: - (Note L) 1272/2008/EC: - (Note L)	- - -	max. 90
Lubricating oils (petroleum), C24-C50* REACH Registr. Nr.: 01-2119489969-06	309-877-7	101316-72-7	67/548/EEC: - (Note L) 1272/2008/EC: Asp. Tox. 1 (Note L)	- H304	
Reaction products of bis(4-methylpentan-2-yl) dithiophosphoric acid with phosphorous oxide, propylene oxide and amines, C12-C14 alkyl (branched)  REACH Registr.Nr.: 01-2119493620-38	931-384-6		67/548/EEC: Xn, N  1272/2008/EC:  Acute Tox. 4 Eye Dam. 1 Skin Sens. 1 Flam. Liq. 3 Aquatic Chronic 2	R 22, R 41, R 43, R 51/53  H302 H318 H317 H226 H411	max. 2

# SAFETY DATA SHEET

MOL-LUB Ltd.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC



Trade name: **MOL Hykomol LS 85W-90 limited slip gear oil**

Version: 2

Latest revision: 26. 08. 2013

Date of issue: 20. 06. 2007

Page: 4/(12)

Name	EINECS number	CAS number	Hazard symbol / Hazard classes and cat.	Risk phrase / Hazard statements	Conc. % (m/m)
Oleilamin 	204-015-5	112-90-3	<i>67/548/EEC:</i> C, N  <i>1272/2008/EC:</i> Acute Tox. 4 Eye Dam. 1 Skin Corr. 1C Skin Sens. 1 Aquatic Acute 1	R 22, R 34, R 43, R 50  H302 H318 H314 H317 H400	max. 0.65
Formaldehyde, reaction products with branched and linear heptylphenol, carbon disulfide and hydrazine 	300-298-5		<i>67/548/EEC:</i> Xi  <i>1272/2008/EC:</i> Eye Dam. 1 Skin Irrit. 2 Skin Sens. 1 Aquatic Chronic 3	R 38, R 41, R 43, R 52/53  H318 H315 H317 H412	max. 0.4

\*: with exposure limit

The full text of each relevant R-, H- phrase and Hazard classes and cat. see in Section 16.

## 4. First aid measures

### 4.1 Description of first aid measures

General information: Never give anything by mouth to an unconscious person, or never induce vomiting.

Inhalation: Remove the affected person to fresh air. If rapid recovery does not occur, obtain medical attention.

Skin contact: Remove contaminated clothing. Wash skin with large amounts of water, use soap. In case of persistent irritation, get medical attention.

Eye contact: Flush eyes with plenty of water for 10-15 minutes. In case of persistent irritation, get medical attention.

Ingestion: If swallowed, give water. **Do not** induce vomiting. Get medical attention.

### 4.2 Most important symptoms and effects, both acute and delayed

No data available.

### 4.3 Indication of any immediate medical attention and special treatment need

Not required.

# SAFETY DATA SHEET

MOL-LUB Ltd.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: **MOL Hykomol LS 85W-90 limited slip gear oil**

Version: 2

Latest revision: 26. 08. 2013

Date of issue: 20. 06. 2007

Page: 5/(12)

## 5. Fire-fighting measures

Fire hazards:

Moderately hazardous (see also Section 9 - flash point).

### 5.1 Extinguishing media

Suitable extinguishing media:

Foam, carbon dioxide, dry chemical powder.

Unsuitable extinguishing media:

Water jet.

### 5.2 Special hazards arising from the mixture

Hazardous combustion products:

On burning, carbon dioxide, carbon monoxide, nitrogen oxides, phosphor oxides, various hydrocarbons and soot can be formed.

### 5.3 Advice for fire-fighters

Special protective equipment:

According to the existing fire-fighting regulations.

Further information:

Collect contaminated fire fighting water separately. It must not enter the sewage system. Contaminated extinguishing water must be disposed of in accordance with official regulations.

## 6. Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: see Section 8.

### 6.2 Environmental precautions:

Confine spills to prevent material from entering sewers, watercourses, drains and into soil Notify relevant authority.

### 6.3 Methods and material for containment and cleaning up

On soil: All kind of ignition sources should be remove. Recover free liquid by pumping. Contain the rest or small quantities with sand, earth or other suitable absorbents. Dispose of according to local regulations.

On water: Confine the spillage. Remove from surface by skimming or suitable absorbents. Notify local authorities according to regulations.

# SAFETY DATA SHEET

MOL-LUB Ltd.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: **MOL Hykomol LS 85W-90 limited slip gear oil**

Version: 2

Latest revision: 26. 08. 2013

Date of issue: 20. 06. 2007

Page: 6/(12)

## 6.4 Reference to other sections

Personal precautions: see section 8.

Waste treatment methods: see section 13.

## 7. Handling and storage

### 7.1 Precautions for safe handling

Keep general measures applied for normal operations with lubricants and flammable liquids.

Keep away from radiant heat and open flame.

Avoid contact with skin and eyes. Avoid prolonged breathing of oil vapours or mists.

Ensure washing facilities after working hours and before breaks. Take off contaminated or oil-soaked clothing, wash with warm water and soap.

When using do not eat, drink or smoke. Avoid splashing the product.

Handling temperature: not known

### 7.2 Conditions for safe storage, including any incompatibilities

Storage facilities must comply with regulations for storing of flammable liquids.

Store in dry, well ventilated place in original, closed containers.

Keep away from radiant heat, open flame and strong oxidizing agents.

Storage temperature: max. 40°C

### 7.3 Specific end use(s)

Gear oil.

## 8. Exposure controls / personal protection

Engineering control measures:

Not required.

### 8.1 Control parameters:

**Mineral oil mist:** TWA: **5 mg/m<sup>3</sup>**; STEL: 10 mg/m<sup>3</sup>, for oil mist, vapour excluded (ACGIH).

Method of testing, recommended: NIOSH 5026

### 8.2 Exposure controls

Personal protection:

Respiratory protection: Breathing apparatus not required.

Hand protection: Oil resistant gloves (EN 374, Breakthrough time 480 min) (e.g. nitrile rubber – minimal thickness 0.33 mm).

Note: Manufacturer's directions for use and the conditions of application should be observed.

# SAFETY DATA SHEET

MOL-LUB Ltd.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: **MOL Hykomol LS 85W-90 limited slip gear oil**

Version: 2

Latest revision: 26. 08. 2013

Date of issue: 20. 06. 2007

Page: 7/(12)

Eye protection: Where splashing is possible, wear safety glasses with side shields.  
Skin protection: Protective clothing (oil resistant).  
Other special: no data

Environmental exposure controls:  
Do not discharge into drains/surface waters/groundwater.

## 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance:

Physical state: liquid  
Colour: brown, clear  
Odour: characteristic

Change in physical state:

Pour point (ISO 3016): typ. -27°C  
Boiling point: not available

Others:

Flash point (COC) (EN ISO 2592): typ. 220°C  
Ignition point (EN ISO 2592): not available  
Autoignition temperature: not available  
Explosive properties: not explosive  
Oxidizing properties: not oxidize  
Vapour pressure at 20°C: negligible  
Density at 15°C (EN ISO 12185): 0.905 – 0.919 g/cm<sup>3</sup>  
Solubility in water: practically insoluble in water  
Solubility in other solvents: gasoline, kerosene, toluene, etc.  
n-Octanol/water partition coefficient: not available  
Vapour density: not available  
Evaporation rate: not available  
Heating value: inf. 38 000 kJ/kg  
Kinematic viscosity at 40°C (EN ISO 3104): typ. 190 mm<sup>2</sup>/s  
Kinematic viscosity at 100°C (EN ISO 3104): typ. 16.5 mm<sup>2</sup>/s  
pH: not applicable

### 9.2 Other information

no data available

# SAFETY DATA SHEET

MOL-LUB Ltd.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: **MOL Hykomol LS 85W-90 limited slip gear oil**

Version: 2

Latest revision: 26. 08. 2013

Date of issue: 20. 06. 2007

Page: 8/(12)

## 10. Stability and reactivity

- 10.1 Reactivity: Dangerous reactivity not known.  
10.2 Chemical stability: No decomposition if stored and handled properly.  
10.3 Possibility of hazardous reactions: Not known.  
10.4 Conditions to avoid: Direct heat or ignition sources.  
10.5 Incompatible materials: Strong oxidizing agents.  
10.6 Hazardous decomposition products: No dangerous decomposition products are formed under normal conditions. Hazardous combustion products: See Section 5.

## 11. Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity:

Oral:	LD <sub>50</sub> (rat)	> 2000	mg/kg	(based on components)
Dermal:	LD <sub>50</sub> (rabbit)	> 2000	mg/kg	(based on components)

Acute toxicity: irritation

- Skin: not irritant (based on components)  
Note: Prolonged and/or repeated contact may cause irritation on skin depending on individual sensitivity  
Eye: irritant (based on components), causes serious eye irritation

Respiratory or skin sensitisation: sensitising (based on components)

Other information, specific effects:

The product does not contain PCBs, PCTs, and other chlorine compounds, and heavy metals, barium compounds.

Note L: The classification as a carcinogen need not apply according to 1272/2008/EC, because it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346.

- Germ cell mutagenicity: not known, resp. not mutagen (based on components)  
Carcinogenicity: not known, resp. not carcinogen (based on components)  
Reproductive toxicity: not known, resp. no reproduction-damaging effect (based on components)  
STOT-single exposure: not known  
STOT-repeated exposure: not known  
Aspiration hazard: not known



# SAFETY DATA SHEET

MOL-LUB Ltd.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: **MOL Hykomol LS 85W-90 limited slip gear oil**

Version: 2

Latest revision: 26. 08. 2013

Date of issue: 20. 06. 2007

Page: 9/(12)

## 12. Ecological information

12.1	Toxicity	No data for the product.
	Aquatic organisms:	
	Soil organisms:	
	Plants:	
12.2	Persistence and degradability	No data available.
	Biodegradability:	No data available.
12.3	Bioaccumulative potential	No data available.
12.4	Mobility	
	Mobility in soil	Absorbs in soil.
	Mobility in water:	Floats on water.
12.5	Results of PBT and vPvB assessment	Not required.
12.6	Other adverse effects	
	Heavy metal content:	None.
	PCT, PCB and other chlorinated hydrocarbons:	None.
	Environmental effects:	Spills may form a film on water surfaces causing impaired oxygen transfer.
	Water hazard class (German):	-

## 13. Disposal considerations

### 13.1 Waste treatment methods

#### Product disposal:

Wastes of the product or used oil should be treated as hazardous waste.

EWC cod: 13 02 05\*

Mineral-based non-chlorinated engine, gear and lubricating oils.

Disposal must be in compliance with national and local regulations.

Recommended waste treatment method: incineration

#### Packaging disposal:

Containers with product residue should also be treated as hazardous waste according to national and local disposal regulations.

EWC cod: 15 01 10\*

Packaging containing residues of or contaminated by dangerous substances.

Disposal must be in compliance with national and local regulations.



# SAFETY DATA SHEET

MOL-LUB Ltd.

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: **MOL Hykomol LS 85W-90 limited slip gear oil**

Version: 2

Latest revision: 26. 08. 2013

Date of issue: 20. 06. 2007

Page: 11/(12)

Source of data presented in this material safety data sheet:

Test results of this product

Material safety data sheets of product's components

Hungarian and EU lists of dangerous substances

Relevant Hungarian regulation and EU directives

Classification for mixtures and used evaluation method according to regulation 1272/2008/EC (CLP)

Eye Irrit. 2                      H319                      calculated method

Skin Sens. 1                      H317                      calculated method

*The full text of each relevant R-, H- phrase and Hazard classes and cat. in Section 3.:*

R 22	Harmful if swallowed.
R 34	Causes burns.
R 38	Irritating to skin.
R 41	Risk of serious damage to eyes.
R 43	May cause sensitisation by skin contact.
R 50	Very toxic to aquatic organisms.
R 51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Flam.Liq. 3	Flammable liquid Category 3
Acute Tox. 4	Acute toxicity Category 4
Asp.Tox.1	Aspiration hazard Category 1

# SAFETY DATA SHEET

**MOL-LUB Ltd.**

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: **MOL Hykomol LS 85W-90 limited slip gear oil**

Version: 2    Latest revision: 26. 08. 2013    Date of issue: 20. 06. 2007    Page: 12/(12)

Skin Corr. 1C	Respiratory/skin sensitization Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Respiratory/skin sensitization Category 1
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Aquatic Acute 1	Hazardous to the aquatic environment, Acute Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, Chronic Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, Chronic Category 3

## Revision Indicators:

Section	Subject of change	Date	Version
2	Hazards identification	26.08.2013	2
3	Composition/information on ingredients		
8	Exposure controls / personal protection		
9	Physical and chemical properties		
11	Toxicological information		
1-16	Revision modification according to 1272/2008/EC and 453/2010/EC		