



SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

MOL-LUB Ltd.

Trade name: **MOL MK 9 15W-40 multigrade diesel motor oil**

Version: 2 Latest revision: 29. 10. 2020 Date of issue: 17. 07. 2019 Page: 1/(15)

SECTION 1 Identification of the mixture/substance and of the company/undertaking

1.1 Product identifier:

MOL MK 9 15W-40 multigrade diesel motor oil

1.2 Relevant identified uses of the mixture or substance and uses advised against

Relevant identified uses: multigrade diesel motor oil.

Uses advised against: no data.

1.3 Details of the supplier of the safety data sheet:

MOL-LUB Lubricant Production Distribution and Service Ltd.

H-2931 Almásfüzitő, Fő út 21., Hungary

Phone / Fax: +36 34 526 330 / +36 34 526 391

E-mail: kenoanyag@mol.hu

Request SDS of:

MOL-LUB Lubricant Production Distribution and Service Ltd.

Customer Service Center

H-2931 Almásfüzitő, Fő út 21., Hungary

Phone / Fax: +36 80 201 296 / +36 34 348 010

Responsible for SDS:

MOL LUB Kft.

Tel: +36 80 201 296

E-mail: EBKHelpdesk@MOL.hu

1.4 Emergency telephone number

Emergency telephone (07-15²⁰ h): +36 34 526 210 (CET) on workdays

Health Toxicological Information Service (ETTSZ 1097 Budapest, Albert Flórián st. 2-6.)

Tel.: +36 80 201 199 (0-24 h, free number, can only be called from Hungary).

+36 1 476 6464 (0-24 h, can be called for a normal fee - also from abroad)

National Health Toxicological Information Service:

SECTION 2 Hazards identification

2.1 Classification of the mixture or substance

Hazard Class and Category: Hazard statement:

Aquatic Chronic 3

H412

Harmful to aquatic life with long lasting effects.



SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

MOL-LUB Ltd.

Trade name: **MOL MK 9 15W-40 multigrade diesel motor oil**

Version: 2 Latest revision: 29. 10. 2020 Date of issue: 17. 07. 2019 Page: 2/(15)

2.2 Label elements

Product identification: Trade name: **MOL MK 9 15W-40 multigrade diesel motor oil**

Hazardous components: -

GHS Pictogram: Not required.

Signal word: Not required.

Hazard statement:

H412 Harmful to aquatic life with long lasting effects.

Supplemental hazard information:

EUH208 Contains Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts. May produce an allergic reaction.

Precautionary statements – General: -

Precautionary statements – Prevention:

P273 Avoid release to the environment.

Precautionary statements – Response: -

Precautionary statements – Storage: -

Precautionary statements – Disposal:

P501 Dispose of contents/container in accordance with national regulation.

Other liabilities for labelling:

Tactile warning of danger: not required.

Transport classification: see section 14.

2.3 Other hazards

The product does not contain any PBT or vPvB substance according to annex XIII of regulation (EC) 1907/2006.



SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

MOL-LUB Ltd.

Trade name: **MOL MK 9 15W-40 multigrade diesel motor oil**

Version: 2 Latest revision: 29. 10. 2020 Date of issue: 17. 07. 2019 Page: 3/(15)

SECTION 3 Composition/information on ingredients

3.2 Mixtures

Chemical description: Mixture of refined mineral base oils containing additives.

Component(s) / Hazardous component(s):

Name	EC number	CAS number	Hazard classes and cat.	Hazard statements	Conc. % (m/m)
Distillates (petroleum), solvent-dewaxed heavy paraffinic* REACH Registr. Nr.: 01-2119471299-27	265-169-7	64742-65-0	- (Note L)		max. 90
Distillates (petroleum), solvent-dewaxed light paraffinic REACH Registr. Nr.: 01-2119480132-48	265-159-2	64742-56-9	Asp. Tox. 1 (Note L)	H304	max. 8.0
Residual oils (petroleum), solvent-dewaxed* REACH Registr. Nr.: 01-2119480472-38	265-166-0	64742-62-7	- (Note L)		max. 5.0
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts** REACH Registr. Nr.: 01-2119493626-26	283-392-8	84605-29-8	Skin Irrit. 2 Eye Dam. 1 Aquatic Chronic 2	H315 H318 H411	max. 1.1
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts REACH Registr. Nr.: 01-2119492616-28	274-263-7	70024-69-0	Skin Sens. 1B	H317	max. 0.6
O,O,O-triphenyl phosphorothioate REACH Registr. Nr.: 01-2119979545-21	209-909-9	597-82-0	Repr. 2	H361fd	max. 0.11
Phenol, dodecyl-, branched REACH Registr. Nr.: 01-2119513207-49	310-154-3	121158-58-5	Skin Corr. 1C Eye Dam. 1 Repr. 1B Aquatic Acute 1 Aquatic Chronic 1	H314 H318 H360F H400 (M=10) H410 (M=10)	max. 0.04

*: with exposure limit

** Specific concentration limit:

Skin Irrit. 2; : 6.25 % ≤ C ≤ 100 %; Eye Irrit. 2; : 10 % < C ≤ 12.5 %;

Eye Dam. 1; : 12.5 % < C ≤ 100 %

The full text of each relevant H- phrase and Hazard classes and cat. see in Section 16.

SAFETY DATA SHEET



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

MOL-LUB Ltd.

Trade name: **MOL MK 9 15W-40 multigrade diesel motor oil**

Version: 2 Latest revision: 29. 10. 2020 Date of issue: 17. 07. 2019 Page: 4/(15)

SECTION 4 First aid measures

4.1 Description of first aid measures

General information: Never give anything by mouth to an unconscious person, or never induce vomiting.

Inhalation: Remove the affected person to fresh air. In case of a complaint, call medical attention.

Skin contact: Remove contaminated clothing. Wash skin with large amounts of water, use soap. In case of a complaint, get medical attention.

Eye contact: Flush eyes with plenty of water for 10-15 minutes. In case of a complaint, get medical attention.

Ingestion: If swallowed, give water. **Do not** induce vomiting. Get medical attention.

Protection of first-aid person: No data available.

4.2 Most important symptoms and effects, both acute and delayed

Prolonged and/or repeated contact may cause irritation on skin or in eyes depending on individual sensitivity.

May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment need

Not required.

SECTION 5 Fire-fighting measures

Fire hazards:

Combustible.

5.1 Extinguishing media

Suitable extinguishing media:

Foam, carbon dioxide, dry chemical powder.

Unsuitable extinguishing media:

Water jet.

5.2 Special hazards arising from the mixture or substance

Hazardous combustion products:

On burning, carbon dioxide, carbon monoxide, sulphur oxides, phosphor oxides, various hydrocarbons and soot can be formed.

SAFETY DATA SHEET



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

MOL-LUB Ltd.

Trade name: **MOL MK 9 15W-40 multigrade diesel motor oil**

Version: 2 Latest revision: 29. 10. 2020 Date of issue: 17. 07. 2019 Page: 5/(15)

5.3 Advice for fire-fighters

Special protective equipment:

According to the existing fire-fighting regulations. Respiratory protection.

Further information:

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Contaminated extinguishing water must be disposed of in accordance with official regulations.

SECTION 6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: see Section 8.

Danger of slipping on leaked out/spilled product.

6.2 Environmental precautions:

Confine spills to prevent material from entering sewers, watercourses, drains and into soil

Notify relevant authority.

6.3 Methods and material for containment and cleaning up

On soil: All kind of ignition sources should be remove. Recover free liquid by pumping. Contain the rest or small quantities with sand, earth or other suitable absorbents. Dispose of according to local regulations.

On water: Confine the spillage. Remove from surface by skimming or suitable absorbents. Notify local authorities according to regulations.

6.4 Reference to other sections

Personal precautions: see section 8.

Waste treatment methods: see section 13.

SECTION 7 Handling and storage

7.1 Precautions for safe handling

Keep general measures applied for normal operations with lubricants and flammable materials.

Keep away from radiant heat and open flame.

Avoid contact with skin and eyes. Avoid prolonged breathing of oil vapours or mists.

Ensure washing facilities after working hours and before breaks. Take off contaminated clothing and wash it before reuse.

When using do not eat, drink or smoke. Avoid splashing the product.

Handling temperature: not known



SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

MOL-LUB Ltd.

Trade name: **MOL MK 9 15W-40 multigrade diesel motor oil**

Version: 2 Latest revision: 29. 10. 2020 Date of issue: 17. 07. 2019 Page: 6/(15)

7.2 Conditions for safe storage, including any incompatibilities
Storage facilities must comply with regulations for storing of flammable liquids.
Store in dry, well ventilated place in original, closed containers.
Keep away from radiant heat, open flame and strong oxidizing agents.
Storage temperature: max. 40°C

7.3 Specific end use(s)
Multigrade diesel motor oil.

SECTION 8 Exposure controls / personal protection

Engineering control measures:
Not required.

8.1 Control parameters:

Mineral oil mist: TWA: **5 mg/m³**; STEL: 10 mg/m³, for oil mist, vapour excluded (ACGIH).

Method of testing, recommended: NIOSH 5026

8.2 Exposure controls

Personal protection:

Respiratory protection: Under normal conditions not required. In case of exceeded exposure-limits respiratory protection with particle-filter is recommended.

Hand protection: Oil resistant gloves (EN 374, Breakthrough time 480 min) (e.g. nitrile rubber – minimal thickness 0.33 mm).

Note: Manufacturer's directions for use and the conditions of application should be observed.

Eye protection: Where splashing is possible, wear safety glasses (EN 166).

Skin protection: Protective clothing (oil resistant).

Other special: no data

Environmental exposure controls:

Do not discharge into drains/surface waters/groundwater.

SECTION 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:

Physical state:	liquid
Colour:	brown, clear
Odour:	characteristic



SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

MOL-LUB Ltd.

Trade name: **MOL MK 9 15W-40 multigrade diesel motor oil**

Version: 2

Latest revision: 29. 10. 2020

Date of issue: 17. 07. 2019

Page: 8/(15)

SECTION 11 Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

Oral:	LD ₅₀ (rat)	> 2000 mg/kg	(based on components)
Dermal:	LD ₅₀ (rabbit)	> 2000 mg/kg	(based on components)

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS: 64742-65-0)

Oral:	LD ₅₀ (rat)	> 5000 mg/kg
Dermal:	LD ₅₀ (rabbit)	> 2000 mg/kg
Inhalation:	LC ₅₀ (rat)	> 5.53 mg/L

Distillates (petroleum), solvent-dewaxed light paraffinic (CAS: 64742-56-9)

Oral:	LD ₅₀ (rat)	> 5000 mg/kg	(literature data)
Dermal:	LD ₅₀ (rabbit)	> 2000 mg/kg	(literature data)
Inhalation:	LC ₅₀ (rat)	> 5.53 mg/L (4 h)	(literature data)

Residual oils (petroleum), solvent-dewaxed (CAS: 64742-62-7)

Oral:	LD ₅₀ (rat)	> 5000 mg/kg	OECD 401
Dermal:	LD ₅₀ (rabbit)	> 5000 mg/kg	OECD 402
Inhalation:	LC ₅₀ (rat)	> 5.53 mg/L (4 h)	OECD 403

Acute toxicity: irritation

Skin:	not irritant (based on components)
Eye:	not irritant (based on components)

Respiratory or skin sensitisation: not sensitising (based on components), but may produce an allergic reaction

Other information, specific effects:

Note L: The classification as a carcinogen need not apply according to 1272/2008/EC, because it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346.

Germ cell mutagenicity:	not known, resp. not mutagen (based on components)
Carcinogenicity:	not known, resp. not carcinogen (based on components)
Reproductive toxicity:	not known, resp. no reproduction-damaging effect (based on components)
STOT-single exposure:	not classified
STOT-repeated exposure:	not classified
Aspiration hazard:	not classified



SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

MOL-LUB Ltd.

Trade name: **MOL MK 9 15W-40 multigrade diesel motor oil**

Version: 2 Latest revision: 29. 10. 2020 Date of issue: 17. 07. 2019 Page: 9/(15)

SECTION 12 Ecological information

12.1 Toxicity No data available for the product.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS: 64742-65-0)

Fishes: LC₅₀ > 100 mg/L

Daphnia: EC₅₀ > 100 mg/L

Other aquatic organisms: EC₅₀ > 100 mg/L

Other living beings: TLM >1 mg/L

Distillates (petroleum), solvent-dewaxed light paraffinic (CAS: 64742-56-9)

Fishes: LC₅₀ > 100 mg/L

Other aquatic organisms: EC₅₀ > 100 mg/L

Algae: ErC₅₀ > 100 mg/L

Crustacea: NOEC >1 mg/L

Residual oils (petroleum), solvent-dewaxed (CAS: 64742-62-7)

Fishes (Pimephales promelas): LL₅₀ >100 mg/L 96 h (OECD 203)

Fishes: NOEL ≥100 mg/L

Daphnia (Daphnia magna): EL₅₀ >10 000 mg/L 48 h (OECD 202)

Daphnia: NOEL ≥1000 mg/L

Daphnia: NOEL 10 mg/L 21 days
(OECD 211)

Gammarus pulex: LL₅₀ >10 000 mg/L 96 h (OECD 202)

Aquatic invertebrates: NOEL ≥10 000 mg/L

Algae (Pseudokirchneriella subcapitata): NOEL ≥100 mg/L 72 h (OECD 201)

Activated sludge

(Photobacterium phosphoreum): NOEL 1.93 mg/L 96 h

Phosphorodithioic acid, mixed O, O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (CAS: 84605-29-8)

Fish (Oncorhynchus mykiss): LC₅₀ 4.5 mg/L 96 h

Fish (Mutton-headed carp): LC₅₀ 46 mg/L 96 h

Fish (Oncorhynchus mykiss): NOEC 1.8 mg/L 96 h

Daphnia: EC₅₀ 23 mg/L 48 h

Daphnia: EC₅₀ >0.8 mg/L 21 days

Daphnia: NOEC 10 mg/L 48 h

Daphnia: NOEC 0.4 mg/L 21 days

Green Algae: EC₅₀ 21 mg/L 72 h

Green Algae: NOEC 10 mg/L 72 h



SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

MOL-LUB Ltd.

Trade name: **MOL MK 9 15W-40 multigrade diesel motor oil**

Version: 2 Latest revision: 29. 10. 2020 Date of issue: 17. 07. 2019 Page: 10/(15)

Phenol, dodecyl-, branched (CAS: 121158-58-5)

Fish (Fat-headed carp):	LC ₅₀	40 mg/L	96 h
Daphnia:	EC ₅₀	0.037 mg/L	48 h
Shrimp (Mysidopsis Bahia):	EC ₅₀	>0.58 mg/L	96 h
Daphnia:	EC ₅₀	0.0079 mg/L	21 days
Daphnia:	NOEC	0.0037 mg/L	21 days
Algae:	EC ₅₀	0.36 mg/L	72 h
Microorganisms (Activated sludge):	EC ₅₀	>1000 mg/L	0.1 days

12.2 Persistence and degradability

Biodegradability: Hydrocarbons are inherently degradable.

Phosphorodithioic acid, mixed O, O-bis(1,3-dimethylbutyl and iso-Pr)esters, zinc salts

1.5% (28 days, OECD TG 301B)

Phenol, dodecyl-, branched

25 % (28 days, OECD TG 301 B)

12.3 Bioaccumulative potential

No data available.

12.4 Mobility

Mobility in soil

Absorbs in soil.

Mobility in water:

Floats on water.

12.5 Results of PBT and vPvB assessment

Does not contain PBT and vPvB substances.

12.6 Other adverse effects

Heavy metal content:

None.

PCT, PCB and other chlorinated hydrocarbons:

None.

Environmental effects:

Harmful to aquatic life with long lasting effects.

Water hazard class (German):

WGK 1 (Classification by AwSV)

SECTION 13 Disposal considerations

13.1 Waste treatment methods

Product disposal:

Wastes of the product or used oil should be treated as hazardous waste.

Waste Identification Code: 13 02 05*

Mineral-based non-chlorinated engine, gear and lubricating oils.

Recommended waste treatment method: incineration



SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

MOL-LUB Ltd.

Trade name: **MOL MK 9 15W-40 multigrade diesel motor oil**

Version: 2 Latest revision: 29. 10. 2020 Date of issue: 17. 07. 2019 Page: 11/(15)

Packaging disposal:

Containers with product residue should also be treated as hazardous waste according to national and local disposal regulations.

Waste Identification Code: 15 01 10*

Packaging containing residues of or contaminated by dangerous substances.

Disposal must be in compliance with national and local regulations.

Wastewater:

Quality of wastewater emitted to natural water must comply with national and local regulations.

Care should be taken in any case to ensure compliance with EC, national and local regulations. It is the responsibility of the user to know all relevant national and local regulations.

SECTION 14 Transport information

Land transport:

Road/ Railway ADR/RID: Not classified.

- | | |
|------------------------------------|-----------------|
| 14.1 UN number: | not classified. |
| 14.2 UN proper shipping name: | not classified. |
| 14.3 Transport hazard class(es): | not classified. |
| 14.4 Packing group: | not classified. |
| 14.5 Environmental hazards: | not classified. |
| 14.6 Special precautions for user: | not classified. |

Waterways:

Inland waterways/ Sea transport ADN/IMDG: Not apply to the product.

Air transport: ICAO / IATA: Not apply to the product.

SECTION 15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the mixture.
This safety data sheet has been prepared according to Regulation (EC) No 1907/2006 (mod.: 2015/830/EU) and to Regulation (EC) 1272/2008.
Seveso category: not classified
- 15.2 Chemical safety assessment.
not available



SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

MOL-LUB Ltd.

Trade name: **MOL MK 9 15W-40 multigrade diesel motor oil**

Version: 2 Latest revision: 29. 10. 2020 Date of issue: 17. 07. 2019 Page: 12/(15)

SECTION 16 Other information

The information given in this data sheet is based on our best knowledge at the time of publication. The information is related only to this product and is intended to assist its safe transport, handling and use. The given physical and chemical parameters describe the product only for the purpose of safety requirements and therefore should not be construed as guaranteeing any specific property of the product or as being part of a product specification or any contract.

The manufacturer or supplier shall not take responsibility for any damages from the use other than recommended or other misuse of the product. It is the responsibility of the user to keep regulatory precautions and observe recommendations for safe use of the product.

Source of data presented in this material safety data sheet:

- Test results of this product
- Material safety data sheets of product's components
- 1272/2008/EC regulation, Annex XVII. of REACH
- Relevant Hungarian and EU regulations

Classification for mixtures and used evaluation method according to regulation 1272/2008/EC (CLP)

Aquatic Chronic 3 H412 calculated

The full text of each relevant H- phrase and Hazard classes and cat. in Section 3.:

- | | |
|--------|--|
| H304 | May be fatal if swallowed and enters airways. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H360F | May damage fertility. |
| H361fd | Suspected of damaging fertility. Suspected of damaging the unborn child. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |



SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

MOL-LUB Ltd.

Trade name: **MOL MK 9 15W-40 multigrade diesel motor oil**

Version: 2 Latest revision: 29. 10. 2020 Date of issue: 17. 07. 2019 Page: 13/(15)

Asp. Tox. 1	Aspiration hazard Category 1
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens 1B	Respiratory/skin sensitization Category 1B
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Repr. 1B	Reproductive toxicity Category 1B
Repr. 2	Reproductive toxicity Category 2
Aquatic Acute 1	Hazardous to the aquatic environment, Acute Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, Chronic Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, Chronic Category 2

Legend:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration Factor
BOD	Biological Oxygen Demand
Bw	Body Weight
C&L	Classification and Labelling
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging (1272/2008/EC)
CMR	Carcinogenic, Mutagenic or toxic to Reproduction
COD	Chemical Oxygen Demand
CSA	Chemical Safety Assessment
CSR	Chemical Safety Report
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
ECHA	European Chemicals Agency
Ex	Effective Concentration x%
ErC50	EC50 in terms of reduction of growth rate
Edx	Effective Dose x%
EC	European Community
EC number	European Community number
ELINCS	European List of Notified Chemical Substances
ES	Exposure Scenario
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LCx	Lethal Concentration x%
LDx	Lethal Dose x%
LOAEC	Lowest Observed Adverse Effect Concentration



SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

MOL-LUB Ltd.

Trade name: **MOL MK 9 15W-40 multigrade diesel motor oil**

Version: 2 Latest revision: 29. 10. 2020 Date of issue: 17. 07. 2019 Page: 14/(15)

Legend:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration Factor
BOD	Biological Oxygen Demand
Bw	Body Weight
C&L	Classification and Labelling
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging (1272/2008/EC)
CMR	Carcinogenic, Mutagenic or toxic to Reproduction
COD	Chemical Oxygen Demand
CSA	Chemical Safety Assessment
CSR	Chemical Safety Report
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
ECHA	European Chemicals Agency
Ec _x	Effective Concentration x%
ErC ₅₀	EC ₅₀ in terms of reduction of growth rate
Ed _x	Effective Dose x%
EC	European Community
EC number	European Community number
ELINCS	European List of Notified Chemical Substances
ES	Exposure Scenario
ESIS	European Chemical Substances Information System
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC _x	Lethal Concentration x%
LD _x	Lethal Dose x%
LOAEC	Lowest Observed Adverse Effect Concentration
LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
NOEC	No observed effect concentration
NOEL	No observed effect level
NLP	No-Longer Polymer
NOAEL	No Observed Adverse Effect Level
OECD	Organisation for Economic Cooperation and Development
PBT	Persistent Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	parts/million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International carriage of Dangerous Goods by Rail



SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

MOL-LUB Ltd.

Trade name: **MOL MK 9 15W-40 multigrade diesel motor oil**

Version: 2 Latest revision: 29. 10. 2020 Date of issue: 17. 07. 2019 Page: 15/(15)

LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
NOEC	No observed effect concentration
NOEL	No observed effect level
NLP	No-Longer Polymer
NOAEL	No Observed Adverse Effect Level
OECD	Organisation for Economic Cooperation and Development
PBT	Persistent Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	parts/million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International carriage of Dangerous Goods by Rail
SVHC	Substance of Very High Concern
UVCB	substance of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bio-accumulative

Revision Indicators:

Section	Subject of change	Date	Version
1.3	Details of the supplier of the safety data sheet	29. 10. 2020	2
3	Composition/information on ingredients		
11	Toxicological information		
12	Ecological information		