



# SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL Hydro HM 46 AL ashless hydraulic oil**

Version: 4

Latest revision: 21. 10. 2015

Date of issue: 20. 06. 2007

Page: 1/(12)

## Section 1 Identification of the mixture and of the company/undertaking

### 1.1 Product identifier:

**MOL Hydro HM 46 AL ashless hydraulic oil**

### 1.2 Relevant identified uses of the mixture and uses advised against

Relevant identified uses: ashless hydraulic oil

Uses advised against: no data

### 1.3 Details of the supplier of the safety data sheet:

MOL-LUB Lubricant Production Trade and Service Limited Liability Company

H-2931 Almásfüzitő, Fő út 21., Hungary

Phone / Fax: +36 34 526 330 / +36 34 526 391

E-mail: kenoanyag@mol.hu

Request SDS of:

MOL-LUB Lubricant Production Trade and Service Limited Liability Company

Customer Service Center

H-2931 Almásfüzitő, Fő út 21., Hungary

Phone / Fax: +36 80 201 296 / +36 34 348 010

Responsible for SDS:

MOL-LUB Ltd. Csaba Horváth, head of SD, HSE & Business Support

Phone: +36 34 526 343; Mobile: +36 20 474 2644

e-mail: csahorvath@mol.hu

### 1.4 Emergency telephone number

Emergency telephone (07-15<sup>20</sup> h): +36 34 526 210 (CET) on workdays

Health Toxicological Information Service (ETTSZ 1096 Budapest, Nagyvárad tér 2.)

Tel.: +36 1 476 6464, or +36 80 201 199

National Health Toxicological Information Service:



# SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL Hydro HM 46 AL ashless hydraulic oil**

Version: 4

Latest revision: 21. 10. 2015

Date of issue: 20. 06. 2007

Page: 2/(12)

## Section 2 Hazards identification

### 2.1 Classification of the mixture

Hazard Class and Category: Hazard statement:  
Not classified. -

### 2.2 Label elements 1272/2008/EC

Product identification: Trade name: **MOL Hydro HM 46 AL ashless hydraulic oil**

Hazardous component(s): -

GHS Pictogram: Not required.

Signal word: Not required.

Hazard statement:

**Not required.**

Supplemental hazard information: -

Precautionary statements – General: -

Precautionary statements – Prevention:

**P273** Avoid release to the environment.

Precautionary statements – Response: -

Precautionary statements – Storage: -

Precautionary statements – Disposal:

**P501** Dispose of contents/container in accordance with national regulation.

Other liabilities for labelling:

Tactile warning of danger: Not required.

Transport classification: see section 14.

### 2.3 Other hazards

The product does not contain any PBT or vPvB substance according to annex XIII of regulation (EC) 1907/2006.



# SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL Hydro HM 46 AL ashless hydraulic oil**

Version: 4

Latest revision: 21. 10. 2015

Date of issue: 20. 06. 2007

Page: 3/(12)

## Section 3 Composition/information on ingredients

### 3.2 Mixtures

Chemical description: Mixture of refined mineral base oils containing additives.

Component(s) / Hazardous component(s):

Name	EU number	CAS number	Hazard classes and cat.	Hazard statements	Conc. % (m/m)
Lubricating oils (petroleum), C24-C50* REACH Registr.Nr.: 01-2119489969-06	309-877-7	101316-72-7	Asp.Tox.1 (Note L)	H304	max. 99
Lubricating oils (petroleum), C18-40* REACH Registr.Nr.: 01-2119486987-11	305-594-8	94733-15-0	Asp.Tox.1 (Note L)	H304	
Lubricating oils (petroleum), C>25* REACH Registr. Nr.: 01-2119486948-13	309-874-0	101316-69-2	- (Note L)	-	max. 30
Lubricating oils (petroleum), C18-40* REACH Registr.Nr.: 01-2119486987-11	305-594-8	94733-15-0	- (Note L)	-	

\*: with exposure limit

The full text of each relevant H- phrase and Hazard classes and cat. see in Section 16.

## Section 4 First aid measures

### 4.1 Description of first aid measures

General information: Never give anything by mouth to an unconscious person, or never induce vomiting.

Inhalation: Remove the affected person to fresh air. If rapid recovery does not occur, obtain medical attention.

Skin contact: Wash skin with large amounts of water, use soap. In case of persistent irritation, get medical attention.



## SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL Hydro HM 46 AL ashless hydraulic oil**

Version: 4

Latest revision: 21. 10. 2015

Date of issue: 20. 06. 2007

Page: 4/(12)

Eye contact: Flush eyes with plenty of water for 10-15 minutes. In case of persistent irritation, get medical attention.

Ingestion: If swallowed, give water. **Do not** induce vomiting. Get medical attention.

Protection of first-aid person: No individual specifications.

4.2 Most important symptoms and effects, both acute and delayed  
No data available.

4.3 Indication of any immediate medical attention and special treatment need  
Not required.

### Section 5 Fire-fighting measures

Fire hazards:  
Combustible.

5.1 Extinguishing media  
Suitable extinguishing media:  
Foam, carbon dioxide, dry chemical powder.

Unsuitable extinguishing media:  
Water jet.

5.2 Special hazards arising from the mixture  
Hazardous combustion products:  
On burning, carbon dioxide, carbon monoxide, various hydrocarbons and soot can be formed.

5.3 Advice for fire-fighters  
Special protective equipment:  
According to the existing fire-fighting regulations.

Further information:  
-



# SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL Hydro HM 46 AL ashless hydraulic oil**

Version: 4

Latest revision: 21. 10. 2015

Date of issue: 20. 06. 2007

Page: 5/(12)

## Section 6 Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: see Section 8.

### 6.2 Environmental precautions:

Confine spills to prevent material from entering sewers, watercourses, drains and into soil Notify relevant authority.

### 6.3 Methods and material for containment and cleaning up

On soil: All kind of ignition sources should be remove. Recover free liquid by pumping. Contain the rest or small quantities with sand, earth or other suitable absorbents. Dispose of according to local regulations.

On water: Confine the spillage. Remove from surface by skimming or suitable absorbents. Notify local authorities according to regulations.

### 6.4 Reference to other sections

Personal precautions: see Section 8.

Waste treatment methods: see Section 13.

## Section 7 Handling and storage

### 7.1 Precautions for safe handling

Keep general measures applied for normal operations with lubricants and flammable liquids.

Keep away from radiant heat and open flame.

Avoid contact with skin and eyes. Avoid prolonged breathing of oil vapours or mists.

Ensure washing facilities after working hours and before breaks. Take off contaminated or oil-soaked clothing, wash with warm water and soap.

When using do not eat, drink or smoke. Avoid splashing the product.

Handling temperature:

### 7.2 Conditions for safe storage, including any incompatibilities

Storage facilities must comply with regulations for storing of flammable liquids.

Store in dry, well ventilated place in original, closed containers.

Keep away from radiant heat, open flame and strong oxidizing agents.

Storage temperature: max. 40°C

### 7.3 Specific end use(s)

Ashless hydraulic oil.



# SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL Hydro HM 46 AL ashless hydraulic oil**

Version: 4

Latest revision: 21. 10. 2015

Date of issue: 20. 06. 2007

Page: 6/(12)

## Section 8 Exposure controls / personal protection

Engineering control measures:

Not required.

8.1 Control parameters:

**Mineral oil mist:** TWA: **5 mg/m<sup>3</sup>**; STEL: 10 mg/m<sup>3</sup>, for oil mist, vapour excluded (ACGIH).

Method of testing, recommended: NIOSH 5026

8.2 Exposure controls

Personal protection:

Respiratory protection: Breathing apparatus not required.

Hand protection: Oil resistant gloves (EN 374, Breakthrough time 480 min) (e.g. nitrile rubber – minimal thickness 0.33 mm).

Note: Manufacturer's directions for use and the conditions of application should be observed.

Eye protection: Protective goggles not required.

Skin protection: Protective clothing (oil resistant).

Other special: no data

Environmental exposure controls:

Do not discharge into drains/surface waters/groundwater.

## Section 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:

Physical state:	liquid
Colour:	yellow, clear
Odour:	characteristic

Change in physical state:

Pour point (ISO 3016):	typ. -30°C
Boiling point (DIN 51356):	not available

Others:

Flash point (COC) (EN ISO 2592):	typ. 225°C
Ignition point (EN ISO 2592):	not available
Autoignition temperature:	not available
Explosive properties:	not explosive
Oxidizing properties:	not oxidize
Vapour pressure at 20°C:	negligible



# SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL Hydro HM 46 AL ashless hydraulic oil**

Version: 4

Latest revision: 21. 10. 2015

Date of issue: 20. 06. 2007

Page: 7/(12)

Density at 15°C (EN ISO 12185):	0.878 g/cm <sup>3</sup>
Solubility in water:	practically insoluble in water
Solubility in other solvents:	gasoline, kerosene, toluene, etc.
n-Octanol/water partition coefficient:	not available
Vapour density:	not available
Heating value:	inf. 38 000 kJ/kg
Kinematic viscosity at 40°C (EN ISO 3104):	typ. 47 mm <sup>2</sup> /s
Kinematic viscosity at 100°C (EN ISO 3104):	typ. 6.8 mm <sup>2</sup> /s
pH:	not applicable

## 9.2 Other information

no data available

## Section 10 Stability and reactivity

10.1 Reactivity:	Dangerous reactivity not known.
10.2 Chemical stability:	No decomposition if stored and handled properly.
10.3 Possibility of hazardous reactions:	Not known.
10.4 Conditions to avoid:	Direct heat or ignition sources.
10.5 Incompatible materials:	Strong oxidizing agents.
10.6 Hazardous decomposition products:	No dangerous decomposition products are formed under normal conditions. Hazardous combustion products: See Section 5.

## Section 11 Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity:

Oral:	LD <sub>50</sub> (rat)	> 5000	mg/kg	(based on components)
Dermal:	LD <sub>50</sub> (rabbit)	> 2000	mg/kg	(based on components)

#### Acute toxicity: irritation

Skin:	not irritant (based on components)
Eye:	not irritant (based on components)
Note:	Prolonged and/or repeated contact may cause irritation on skin or in eyes depending on individual sensitivity.

Respiratory or skin sensitisation: not sensitising (based on components)



# SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL Hydro HM 46 AL ashless hydraulic oil**

Version: 4

Latest revision: 21. 10. 2015

Date of issue: 20. 06. 2007

Page: 8/(12)

## Other information, specific effects:

The product does not contain PCBs, PCTs, and other chlorine compounds, and heavy metals, barium compounds.

Note L: The classification as a carcinogen need not apply according to 1272/2008/EC, because it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346.

Germ cell mutagenicity:	not known, resp. not mutagen (based on components)
Carcinogenicity:	not known, resp. not carcinogen (based on components)
Reproductive toxicity:	not known, resp. no reproduction-damaging effect (based on components)
STOT-single exposure:	not known
STOT-repeated exposure:	not known
Aspiration hazard:	not known

## Section 12 Ecological information

12.1 Toxicity	Not available.
Aquatic organisms:	
Soil organisms:	
Plants:	
12.2 Persistence and degradability	No data available.
Biodegradability:	No data available.
12.3 Bioaccumulative potential	No data available.
12.4 Mobility	
Mobility in soil	Absorbs in soil.
Mobility in water:	Floats on water.
12.5 Results of PBT and vPvB assessment	Does not contain PBT and vPvB substances.
12.6 Other adverse effects	
Heavy metal content:	None.
PCT, PCB and other chlorinated hydrocarbons:	None.
Environmental effects:	Spills may form a film on water surfaces causing impaired oxygen transfer.
Water hazard class (German):	WGK 1 (Classification by VwVwS)





# SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL Hydro HM 46 AL ashless hydraulic oil**

Version: 4

Latest revision: 21. 10. 2015

Date of issue: 20. 06. 2007

Page: 9/(12)

## Section 13 Disposal considerations

### 13.1 Waste treatment methods

#### Product disposal:

Wastes of the product or used oil should be treated as hazardous waste.

Waste Identification Code: 13 01 10\*

Mineral based non-chlorinated hydraulic oils.

Waste Identification Code: 13 02 05\*

Mineral-based non-chlorinated engine, gear and lubricating oils.

Disposal must be in compliance with national and local regulations.

Recommended waste treatment method: incineration

#### Packaging disposal:

Containers with product residue should also be treated as hazardous waste according to national and local disposal regulations.

Waste Identification Code: 15 01 10\*

Packaging containing residues of or contaminated by dangerous substances.

Disposal must be in compliance with national and local regulations.

Recommended waste treatment method: incineration

#### Wastewater:

Quality of wastewater emitted to natural water must comply with national and local regulations.

Care should be taken in any case to ensure compliance with EC, national and local regulations. It is the responsibility of the user to know all relevant national and local regulations.

## Section 14 Transport information

### Land transport:

Road/ Railway

ADR/RID:

Not classified.

14.1. UN number: -

14.2. UN proper shipping name: -

14.3. Transport hazard class(es): -

14.4. Packing group: -

14.5. Environmental hazards: -

14.6. Special precautions for user: -



## SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL Hydro HM 46 AL ashless hydraulic oil**

Version: 4

Latest revision: 21. 10. 2015

Date of issue: 20. 06. 2007

Page: 10/(12)

Waterways:

Inland waterways/ Sea transport ADN/IMDG: Not apply to the product.

Air transport:

ICAO / IATA: Not apply to the product.

### Section 15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

This safety data sheet has been prepared according to Regulation (EC) No 1907/2006 (applicable version) and to Regulation (EC) 1272/2008.

15.2 Chemical safety assessment.  
not available

### Section 16 Other information

The information given in this data sheet is based on our best knowledge at the time of publication. The information is related only to this product and is intended to assist its safe transport, handling and use. The given physical and chemical parameters describe the product only for the purpose of safety requirements and therefore should not be construed as guaranteeing any specific property of the product or as being part of a product specification or any contract.

The manufacturer or supplier shall not take responsibility for any damages from the use other than recommended or other misuse of the product. It is the responsibility of the user to keep regulatory precautions and observe recommendations for safe use of the product.

Source of data presented in this material safety data sheet:

Test results of this product

Material safety data sheets of product's components

Hungarian and EU lists of dangerous substances

Relevant Hungarian regulation and EU directives

Classification for mixtures and used evaluation method according to regulation 1272/2008/EC (CLP)

Not classified. -



## SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL Hydro HM 46 AL ashless hydraulic oil**

Version: 4

Latest revision: 21. 10. 2015

Date of issue: 20. 06. 2007

Page: 11/(12)

*The full text of each relevant H- phrase and Hazard classes and cat. in Section 3.:*

H304                      May be fatal if swallowed and enters airways.

Asp.Tox.1                Aspiration hazard Category 1

### Legend:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration Factor
BOD	Biological Oxygen Demand
Bw	Body Weight
C&L	Classification and Labeling
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic or toxic to Reproduction
COD	Chemical Oxygen Demand
CSA	Chemical Safety Assessment
CSR	Chemical Safety Report
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
ECHA	European Chemicals Agency
Ec <sub>x</sub>	Effective Concentration x%
Ed <sub>x</sub>	Effective Dose x%
ELINCS	European List of Notified Chemical Substances
ErC <sub>50</sub>	EC <sub>50</sub> in terms of reduction of growth rate;
ES	Exposure Scenario
ESIS	European Chemical Substances Information System
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC <sub>x</sub>	Lethal Concentration x%
LD <sub>x</sub>	Lethal Dose x%
LOAEC	Lowest Observed Adverse Effect Concentration
LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
NOEC	No observed effect concentration
NOEL	No observed effect level
NLP	No-Longer Polymer
NOAEL	No Observed Adverse Effect Level



# SAFETY DATA SHEET

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

**MOL-LUB Ltd.**

Trade name: **MOL Hydro HM 46 AL ashless hydraulic oil**

Version: 4

Latest revision: 21. 10. 2015

Date of issue: 20. 06. 2007

Page: 12/(12)

OECD	Organisation for Economic Cooperation and Development
PBT	Persistent Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SVHC	Substance of Very High Concern
UVCB	substance of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bio-accumulative

## Revision Indicators:

Section	Subject of change	Date	Version
1-16	Revision modification according to REACH (1907/2006/EC), other correction	29.01.2010	2
3 9 1-16	Composition/information on ingredients Physical and chemical properties Revision modification according to 1272/2008/EC and 453/2010/EC	11.04.2012	3
1 3 9 1-16	Details of the supplier of the safety data sheet, Responsible for SDS Composition/information on ingredients Physical and chemical properties Other corrections, revision modification according to 2015/830 /EU	21.10.2015	4