

according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: MOL DOT 3 Brake fluid

Version: 5 Latest revision: 18. 12. 2020 Date of issue: 03. 02. 2015 Page: 1/(13)

SECTION 1 Identification of the mixture and of the company/undertaking

1.1 Product identifier:

MOL DOT 3 Brake fluid

UFI: F800-D0QG-R00U-D9WR

1.2 Relevant identified uses of the mixture or substance and uses advised against

Relevant identified uses: brake fluid.

Uses advised against: no data.

1.3 Details of the supplier of the safety data sheet:

MOL-LUB Lubricant Production Distribution and Service Ltd.

H-2931 Almásfüzitő, Fő út 21., Hungary

Phone / Fax: +36 34 526 330 / +36 34 526 391

E-mail: kenoanyag@mol.hu

Request SDS of:

MOL-LUB Lubricant Production Distribution and Service Ltd.

Customer Service Center

H-2931 Almásfüzitő, Fő út 21., Hungary

Phone / Fax: +36 80 201 296 / +36 34 348 010

Responsible for SDS:

MOL LUB Kft.

Phone: +36 80 201 296

E-mail: EBKHelpdesk@MOL.hu

1.4 Emergency telephone number

Emergency telephone (07-15²⁰ h): +36 34 526 210 (CET) on workdays

Health Toxicological Information Service (ETTSZ 1097 Budapest, Albert Flórián st. 2-6.)

Tel.: +36 80 201 199 (0-24 h, free number, can only be called from Hungary).

+36 1 476 6464 (0-24 h, can be called for a normal fee - also from abroad)

National Health Toxicological Information Service:

SECTION 2 Hazards identification

2.1 Classification of the mixture or substance

Hazard Class and Category: Hazard statement:

Eye Irrit. 2 H319 Causes serious eye irritation.

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to kidneys through

prolonged or repeated exposure if swallowed.



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: MOL DOT 3 Brake fluid

Version: 5 Latest revision: 18. 12. 2020 Date of issue: 03. 02. 2015 Page: 2/(13)

2.2 Label elements

Product identification: Trade name: MOL DOT 3 Brake fluid

Hazardous components: Diethylene glycol;

Tris[2-[2-(2-methoxyethoxy) ethoxy]ethyl] orthoborate

GHS Pictogram:





Signal word: Warning

Hazard statement:

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H373 May cause damage to kidneys through prolonged or repeated exposure if

swallowed.

Supplemental hazard information: -

Precautionary statements – General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements – Prevention:

P264 Wash hands thoroughly after handling.

Precautionary statements – Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/....
P305 + P351 + IF IN EYES: Rinse cautiously with water for several minutes. Remove

P338 contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/attention.

Precautionary statements – Storage: -

Precautionary statements – Disposal:

P501 Dispose of contents/container in accordance with national regulation.

Other liabilities for labelling:

Tactile warning of danger: distribution for population.

Transport classification: see section 14.



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: MOL DOT 3 Brake fluid

Version: 5 Latest revision: 18. 12. 2020 Date of issue: 03. 02. 2015 Page: 3/(13)

2.3 Other hazards

The product does not contain any PBT or vPvB substance according to annex XIII of regulation (EC) 1907/2006.

SECTION 3 Composition/information on ingredients

3.2 Mixtures

Chemical description: Mixture of the substance.

Component(s) / Hazardous component(s):

Name	EC	CAS	Hazard classes	Hazard	Conc.
1 valle	number	number	and cat.	statements	%(m/m)
Triethylene glycol	205-592-6	143-22-6	Eye Dam. 1	H318	20-29.9
monobutyl ether*					
REACH Registr. Nr.:					
01-2119531322-53					
Diethylene glycol	203-872-2	111-46-6	Acute Tox. 4	H302	10-24
REACH Registr. Nr.:			STOT RE 2	H373	
01-2119457857-21					
Tris[2-[2-(2-methoxyethoxy)	250-418-4	30989-05-0	Repr. 2	H361d	5-20
ethoxy]ethyl] orthoborate					
REACH Registr. Nr.:					
01-2119462824-33					
Poly(oxy-1,2-ethanediyl), α-	500-012-0	9004-77-7	Eye Irrit. 2	H319	5-10
butyl-ω-hydroxy-					
REACH Registr. Nr.:					
01-2119475115-41					
2-(2-butoxyethoxy) ethanol	203-961-6	112-34-5	Eye Irrit. 2	H319	0-2,99
REACH Registr. Nr.:					
01-2119475104-44					
2-(2-Methoxyethoxy) etanol	203-906-6	111-77-3	Repr. 2	H361d	0-2,99
REACH Registr. Nr.:					
01-2119475100-52					

^{*} Specific concentration limit:

Eye Irrit. 2; H319: 20 % \leq C < 30 %; Eye Dam. 1; H318: C \geq 30 %

The full text of each relevant H- phrase and Hazard classes and cat. see in Section 16.



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: MOL DOT 3 Brake fluid

Version: 5 Latest revision: 18. 12. 2020 Date of issue: 03. 02. 2015 Page: 4/(13)

SECTION 4 First aid measures

4.1 Description of first aid measures

General information: Never give anything by mouth to an unconscious person, or never

induce vomiting.

Inhalation: Remove the affected person to fresh air. Keep him warm. Keep at rest. If

symptoms persist, call medical attention.

Skin contact: Remove contaminated clothing and wash skin with plenty of water, use soap.

Do not use solvents or thinners. In case of complaints, get medical attention.

Eye contact: Wash affected eyes for at least 10-15 minutes under running water or with

isotonic water (20-30 ° C), with eyelids held open. Remove contact lenses, if present and easy to do. Get medical attention. Continue rinsing during transport.

Ingestion: If swallowed rinse mouth, give to drink plenty of water.

If medical treatment is delayed, drink 90-120 ml of 40% alcohol (e.g. liqueur) for an adult. Children should be given 2 ml / kg body weight. Do not induce vomiting unless directed to do so by your doctor. In case of spontaneous vomiting, the head should be turn down. Get medical attention immediately.

Protection of first-aid person: No individual specifications.

4.2 Most important symptoms and effects, both acute and delayed

Ingestion of large quantities: renal failure, coma, death. Other symptoms include central nervous system effects, abdominal discomfort, metabolic acidosis, headache and nausea. Inhalation: unlikely route of exposure. May cause respiratory irritation at high temperatures or in aerosol form. See also Ingestion.

Skin: May be absorbed by prolonged contact with damaged skin.

Prolonged contact degreases the skin, causing dermatitis.

Causes serious eye irritation.

May cause damage to kidneys through prolonged or repeated exposure if swallowed.

4.3 Indication of any immediate medical attention and special treatment need

Treat according to symptoms (decontamination, vital functions), no known specific antidote. May cause symptoms similar to ethylene glycol.

SECTION 5 Fire-fighting measures

Fire hazards:

Combustible.



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: **MOL DOT 3 Brake fluid**

Version: 5 Latest revision: 18. 12. 2020 Date of issue: 03. 02. 2015 Page: 5/(13)

5.1 Extinguishing media

Suitable extinguishing media:

Alcohol resistant foam, carbon dioxide, dry chemical powder, water spray (fog).

Unsuitable extinguishing media:

Water jet.

5.2 Special hazards arising from the mixture or substance

Hazardous combustion products:

On burning carbon dioxide, carbon monoxide and other toxic fumes / gases can be formed.

5.3 Advice for fire-fighters

Special protective equipment:

According to the existing fire-fighting regulations (breathing apparatus).

Further information:

In case or fire, keep containers cool with water spray.

Collect contaminated fire fighting water separately. It must not enter drains.

Contaminated extinguishing water must be disposed of in accordance with official regulations.

SECTION 6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: see Section 8.

Keep unnecessary personnel away.

Avoid contact with eyes, skin and clothing.

Danger of slipping on leaked out/spilled product.

Adequate ventilation required.

6.2 Environmental precautions:

Prevent spills from entering into natural water, soil and drains by containing the liquid. Notify relevant authority.

6.3 Methods and material for containment and cleaning up

On soil: Contain spilled liquid with sand, earth or other suitable absorbents. Recover

free liquid by pumping. Dispose of according to local regulations.

For smaller spills, rags or absorbent granules may be used. Do not use

solvents.

On water: Confine the spillage. Notify local authorities according to regulations.

6.4 Reference to other sections

Personal precautions: see section 8.

Waste treatment methods: see section 13.



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: **MOL DOT 3 Brake fluid**

Version: 5 Latest revision: 18. 12. 2020 Date of issue: 03. 02. 2015 Page: 6/(13)

SECTION 7 Handling and storage

7.1 Precautions for safe handling

Keep general measures applied for normal operations with chemicals.

Use in a well-ventilated area.

Avoid contact with skin and eyes. Avoid prolonged breathing of oil vapours or aerosol formation.

Keep unused containers closed (the liquid absorbs the humidity of the air).

Ensure washing facilities after working hours and before breaks. Take off contaminated clothing and wash it before reuse.

When using do not eat, drink or smoke. Avoid splashing the product.

Handling temperature: no data

7.2 Conditions for safe storage, including any incompatibilities

Storage facilities must comply with regulations for storing of chemicals.

Store in cool, dry, well-ventilated area, in original, tightly closed containers.

Strong oxidizing agents, mineral oils be stored separately.

Suitable container material: mild steel, stainless steel.

Always store in a container made of the same material as the material of the original container.

Storage temperature: 15-30°C

7.3 Specific end use(s)

Brake fluid.

SECTION 8 Exposure controls / personal protection

Engineering control measures:

Adequate ventilation (general and local exhaust).

8.1 Control parameters:

EU limits

2-(2-Methoxyethoxy) etanol: TWA (Time weighted average): 50.1 mg/m³ EU2

CAS: 111-77-3

2-(2-butoxyethoxy) ethanol: 10 ppm 15 ppm

CAS: 112-34-5 670 mg/m^3 101.2 mg/m^3



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: **MOL DOT 3 Brake fluid**

Version: 5 Latest revision: 18. 12. 2020 Date of issue: 03. 02. 2015 Page: 7/(13)

8.2 Exposure controls

Personal protection:

Respiratory protection: Under normal conditions not required.

When concentrations in air may exceed the limits recommended

to use a half face filter mask to protect from

overexposure by inhalation. (organic vapor against filter: A-P2)

Chemical resistant gloves are recommended (EN 374-2, 374-3, Hand protection:

388),

Material: Butyl

Layer thickness: 0.3 mm. Breakthrough time: 480 minutes.

Material: Nitrile

Layer thickness: 0.2 mm. Breakthrough time: 480 minutes.

Note: Manufacturer's directions for use and the conditions of

application should be observed.

Eye protection: Safety glasses with side-shields (EN 166) in case of splashes.

Skin protection: Protective clothing.

Other special: An emergency shower and eye wash station shall be available at

the workplace.

Environmental exposure controls:

Do not discharge into drains/surface waters/groundwater.

SECTION 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:

Physical state: liquid

Colour (ASTM D 1500): amber yellow

Odour: mild

Change in physical state:

Initial boiling point / boiling range: >210°C Melting point: <-50°C

Others:

Flash point: $>100^{\circ}$ C Ignition temperature: >280°C Decomposition temperature: >300°C Autoignition temperature: no data Explosive properties: no data Oxidizing properties: no data

Vapour pressure at 20°C: 1.00 mbar



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: MOL DOT 3 Brake fluid

Version: 5 Latest revision: 18. 12. 2020 Date of issue: 03. 02. 2015 Page: 8/(13)

Evaporation rate: 0.01

Density at 20° C: $1.010 - 1.060 \text{ g/cm}^3$ Solubility in water: miscible with water

Solubility in polar solvents: no data n-Octanol/water partition coefficient 1.50

Kinematic viscosity: approx. 5-10 cSt (20°C)

pH at 20° C: 7.0 - 10.5 Solvent content: no data

9.2 Other information

no data available

SECTION 10 Stability and reactivity

10.1 Reactivity: Dangerous reactivity not known.

10.2 Chemical stability: No decomposition if stored and handled properly.

10.3 Possibility of hazardous reactions: Not known.10.4 Conditions to avoid: Not known.

10.5 Incompatible materials: Strong acids, bases, oxidizing agents, reducing agents.

10.6 Hazardous decomposition products: No dangerous decomposition products are formed under

normal conditions. Hazardous combustion products: See

Section 5.

SECTION 11 Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

Oral: LD_{50} (rat) ≥ 5000 mg/kg Dermal: LD_{50} (rabbit) ≥ 3000 mg/kg

Acute toxicity: irritation

Skin: not irritant (based on components)
Eye: irritant (based on components)

Respiratory or skin sensitisation: not sensitising (based on components)



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: **MOL DOT 3 Brake fluid**

Version: 5 Latest revision: 18. 12. 2020 Date of issue: 03. 02. 2015 Page: 9/(13)

Other information, specific effects:

Germ cell mutagenicity: not known, resp. not mutagen (based on components)
Carcinogenicity: not known, resp. not carcinogen (based on components)

Reproductive toxicity: Suspected of damaging the unborn child.

STOT-single exposure: not classified

STOT-repeated exposure: May cause damage to kidneys through prolonged or

repeated exposure if swallowed.

Aspiration hazard: not classified

SECTION 12 Ecological information

12.1 Toxicity

Fish (Oncorhynchus mykiss): LC_{50} > 100 mg/L/96 h

12.2 Persistence and degradability

Biodegradability: The product is inherently degradable. Expected to be

easily degradable (based on components, OECD

302B)

12.3 Bioaccumulative potential Log Pow: \leq 2.0 (each main component).

12.4 Mobility

Mobility in soil: Mobile in the soil until degradation.

Mobility in water: It is completely miscible with water. Evaporation is

not expected.

12.5 Results of PBT and vPvB assessment Does not contain PBT and vPvB substances.

12.6 Other adverse effects

Environmental effects: Large spills may be hazardous to the environment.

Water hazard class (German): No data.

SECTION 13 Disposal considerations

13.1 Waste treatment methods

Product disposal:

Wastes of the product or used oil should be treated as hazardous waste.

Waste Identification Code: 16 01 13*

Brake fluids.

Recommended waste treatment method: Must be dumper or incinerated in accordance with

local regulations.



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: **MOL DOT 3 Brake fluid**

Version: 5 Latest revision: 18. 12. 2020 Date of issue: 03. 02. 2015 Page: 10/(13)

Packaging disposal:

Containers with product residue should also be treated as hazardous waste according to national and local disposal regulations.

Waste Identification Code: 15 01 10*

Packaging containing residues of or contaminated by dangerous substances.

Uncontaminated pack can be re-used.

Packs that cannot be cleaned should be disposed of in the same manner as the contents.

Disposal must be in compliance with national and local regulations.

Wastewater:

Quality of wastewater emitted to natural water must comply with national and local regulations.

Care should be taken in any case to ensure compliance with EC, national and local regulations. It is the responsibility of the user to know all relevant national and local regulations.

SECTION 14 Transport information

Land transport:

ADR/RID: Not classified. Road/ Railway 14.1 UN number: not classified. 14.2 UN proper shipping name: not classified. 14.3 Transport hazard class(es): not classified. 14.4 Packing group: not classified. 14.5 Environmental hazards: not classified. 14.6 Special precautions for user: not classified.

Waterways:

Inland waterways/ Sea transport ADN/IMDG: Not apply to the product. Air transport: ICAO / IATA: Not apply to the product.

SECTION 15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the mixture. This safety data sheet has been prepared according to Regulation (EC) No 1907/2006 (mod.: 2015/830/EU) and to Regulation (EC) 1272/2008.

Seveso category: not classified.

15.2 Chemical safety assessment.

not available



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: MOL DOT 3 Brake fluid

Version: 5 Latest revision: 18. 12. 2020 Date of issue: 03. 02. 2015 Page: 11/(13)

SECTION 16 Other information

The information given in this data sheet is based on our best knowledge at the time of publication. The information is related only to this product and is intended to assist its safe transport, handling and use. The given physical and chemical parameters describe the product only for the purpose of safety requirements and therefore should not be construed as guaranteeing any specific property of the product or as being part of a product specification or any contract.

The manufacturer or supplier shall not take responsibility for any damages from the use other than recommended or other misuse of the product. It is the responsibility of the user to keep regulatory precautions and observe recommendations for safe use of the product.

Source of data presented in this material safety data sheet:

Test results of this product

Material safety data sheets of product's components 1272/2008/EC regulation, Annex XVII. of REACH

Relevant Hungarian and EU regulations

Classification for mixtures and used evaluation method according to regulation 1272/2008/EC

(CLP)

Eye Irrit. 2 H319 based on test results

Repr. 2 H361d calculated STOT RE 2 H373 calculated

The full text of each relevant H- phrase and Hazard classes and cat. in Section 3.:

H302 Harmful if swallowed.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H373 May cause damage to kidneys through prolonged or repeated exposure if

swallowed.

Acute Tox. 4 Acute toxicity Category 4

Eye Dam. 1 Serious eye damage/eye irritation Category 1 Eye Irrit. 2 Serious eye damage/eye irritation Category 2

Repr. 2 Reproductive toxicity Category 2

STOT RE 2 Specific target organ toxicity – repeated exposure Category 2



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

MOL-LUB Ltd.

Trade name: MOL DOT 3 Brake fluid

Version: 5 Latest revision: 18. 12. 2020 Date of issue: 03. 02. 2015 Page: 12/(13)

Legend:

ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland

Waterways

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE Acute Toxicity Estimate
BCF Bioconcentration Factor
BOD Biological Oxygen Demand

Bw Body Weight

C&L Classification and Labelling CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging

CMR Carcinogenic, Mutagenic or toxic to Reproduction

COD Chemical Oxygen Demand
CSA Chemical Safety Assessment
CSR Chemical Safety Report
DMEL Derived Minimal Effect Level
DNEL Derived No Effect Level
ECHA European Chemicals Agency
Ecx Effective Concentration x%

Edx Effective Dose x%

ELINCS European List of Notified Chemical Substances ErC50 EC50 in terms of reduction of growth rate;

ES Exposure Scenario

IARC International Agency for Research on Cancer
IATA International Air Transport Association
IMDG International Maritime Dangerous Goods

LCx Lethal Concentration x%

LDx Lethal Dose x%

LOAEC Lowest Observed Adverse Effect Concentration

LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level NOEC No observed effect concentration

NOEL No observed effect level NLP No-Longer Polymer

NOAEL No Observed Adverse Effect Level

OECD Organisation for Economic Cooperation and Development

PBT Persistent Bioaccumulative and Toxic PNEC Predicted No-Effect Concentration

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Regulations concerning the International Carriage of Dangerous Goods by Rail

SVHC Substance of Very High Concern

UVCB substance of unknown or variable composition, complex reaction products or biological

materials

VOC Volatile organic compounds

vPvB Very Persistent and very Bio-accumulative



according to regulation 1907/2006/EC (REACH) and 1272/2008/EC

Trade name: MOL DOT 3 Brake fluid

Version: 5 Latest revision: 18. 12. 2020 Date of issue: 03. 02. 2015 Page: 13/(13)

Revision Indicators:

C4:	Calling of all and	Data	V
Section	Subject of change	Date	Version
1	Responsible for SDS	10. 04. 2015	2
2	Other hazards		
5	Fire hazards		
14	Transport information		
1-16	Full revision. According to 2015/830 /EU.	14. 05. 2018	3
2.2	Label elements		
3	Composition/information on ingredients		
1-16	Full revision due to changes in composition	01. 11. 2018	4
1	Identification of the mixture and of the	18. 12. 2020	5
	company/undertaking		
2	Hazards identification		
3	Composition/information on ingredients		
4	First aid measures		
6	Accidental release measures		
7	Handling and storage		
8	Exposure controls / personal protection		
9	Physical and chemical properties		
10	Stability and reactivity		
11	Toxicological information		
12	Ecological information		
1-16	Other corrections		