

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Transfluid TO-4 SAE 30 gear oil

Version: 6 Latest revision: 25. 09. 2020 Date of issue: 16. 09. 2008

Page: 1/(13)

#### **SECTION 1** Identification of the mixture/substance and of the company/undertaking 1.1 Product identifier: MOL Transfluid TO-4 SAE 30 gear oil 1.2 Relevant identified uses of the mixture or substance and uses advised against Relevant identified uses: gear oil. Uses advised against: no data. 1.3 Details of the supplier of the safety data sheet: MOL-LUB Lubricant Production Distribution and Service Ltd. H-2931 Almásfüzitő, Fő út 21., Hungary Phone / Fax: +36 34 526 330 / +36 34 526 391 E-mail: kenoanyag@mol.hu Request SDS of: MOL-LUB Lubricant Production Distribution and Service Ltd. **Customer Service Center** H-2931 Almásfüzitő, Fő út 21., Hungary Phone / Fax: +36 80 201 296 / +36 34 348 010 **Responsible for SDS:** MOL-LUB Ltd. Phone: +36 80 201 296 e-mail: EBKHelpdesk@MOL.hu 1.4 Emergency telephone number Emergency telephone (07-15<sup>20</sup> h): +36 34 526 210 (CET) on workdays Health Toxicological Information Service (ETTSZ 1096 Budapest, Nagyvárad tér 2.) Tel.: +36 80 201 199 (0-24 h, free number). National Health Toxicological Information Service:

### SECTION 2 Hazards identification

2.1	Classification of the <u>mixture</u> or substance				
	Hazard Class and Category:	Hazard Class and Category: Hazard statement:			
	Eye Irrit. 2	H319	Causes serious eye irritation.		
	Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.		



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

# Trade name: MOL Transfluid TO-4 SAE 30 gear oil

Version: 6 Latest revision: 25. 09. 2020 Date of issue: 16. 09. 2008

Page: 2/(13)

2.2	Label elements			
	Product ident	fication: Trade name: MOL Transfluid TO-4 SAE 30 gear oil		
	Hazardous component(s): -			
	GHS Pictogram:			
	Signal word:	Warning		
	Hazard staten H319 H412	ent: Causes serious eye irritation. Harmful to aquatic life with long lasting effects.		
	Supplemental	hazard information: -		
	Precautionary statements – General:P101If medical advice is needed, have product container or label at hand.P102Keep out of reach of children.			
	Precautionary statements – Prevention:P273Avoid release to the environment.P280Wear eye protection.			
contact lenses, if present and easy to do. Continue rinsing		<b>+ P338</b> IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
	P337 + P313If eye irritation persists: Get medical advice/attention.			
	Precautionary statements – Storage: -			
	Precautionary statements – Disposal: <b>P501</b> Dispose of contents/container in accordance with national regulation.			
	Other liabilities for labelling: Tactile warning of danger: Not required. Transport classification: see section 14.			
2.3	Other hazards The product d (EC) 1907/20	pes not contain any PBT or vPvB substance according to annex XIII of regulation 06.		



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Transfluid TO-4 SAE 30 gear oil

Version: 6 Latest revision: 25. 09. 2020 Date of issue: 16. 09. 2008

Page: 3/(13)

### SECTION 3 Composition/information on ingredients

#### 3.2 Mixtures

Chemical description:

Mixture of refined mineral base oils containing additives.

Component(s) / Hazardous component(s):

Name	EU	CAS	Hazard classes and	Hazard	Conc.
Lubricating oils	number 309-877-7	number 101316-72-7	cat.	statements	<u>%(m/m)</u> max. 95
(petroleum), C24- C50*	309-877-7	101310-72-7	(Note L)	-	max. 95
REACH Registr. Nr.:			(11000 2)		
01-2119489969-06					
Lubricating oils	309-874-0	101316-69-2	-	-	max. 25
(petroleum), C>25*			(Note L)		
REACH Registr. Nr.:					
01-2119486948-13					
Lubricating oils	305-594-8	94733-15-0	-	-	max. 15
(petroleum), C18-40*			(Note L)		
REACH Registr. Nr.:					
01-2119486987-11	224 225 5	4250 15 0		11210	1.2
Zinc bis[O,O-bis(2-	224-235-5	4259-15-8	Eye Dam. 1	H318	max. 1.3
ethylhexyl)] bis(dithiophosphate)			Aquatic Chronic 2	H411	
REACH Registr. Nr.:					
01-2119493635-27					
Phenol, dodecyl-,	272-234-3	68784-26-9	Aquatic Chronic 4	H413	max. 1.3
sulfurized, carbonates,	212 234 3	00704 20 9	Aquatic Chronic 4	11415	max. 1.5
calcium salts, overbased					
REACH Registr. Nr.:					
01-2119524004-56					
Phenol, dodecyl-, branched	310-154-3	121158-58-5	Skin Corr. 1C	H314	< 0.2
REACH Registr. Nr.:			Eye Dam. 1	H318	
01-2119513207-49			Repr. 1B	H360F	
			Aquatic Acute1	H400 (M=10)	
			Aquatic Chronic 1	H410 (M=10)	

\*: with exposure limit

The full text of each relevant H- phrase, Hazard classes and cat. see in Section 16.



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Transfluid TO-4 SAE 30 gear oil

Version: 6 Latest revision: 25. 09. 2020 Date of issue: 16. 09. 2008

Page: 4/(13)

#### SECTION 4 First aid measures

- 4.1 Description of first aid measures
  - General information: Never give anything by mouth to an unconscious person, or never induce vomiting.
    - Inhalation: Remove the affected person to fresh air. If rapid recovery does not occur, obtain medical attention.
    - Skin contact: Remove contaminated clothing. Wash skin with large amounts of water, use soap. In case of persistent irritation, get medical attention.
    - Eye contact: Flush eyes with plenty of water for 10-15 minutes. In case of persistent irritation, get medical attention.
    - Ingestion: If swallowed, give water. Do not induce vomiting. Get medical attention.

Protection of first-aid person: No individual specifications.

- 4.2 Most important symptoms and effects, both acute and delayed Causes serious eye irritation.
   Prolonged and/or repeated contact may cause irritation on skin depending on individual sensitivity.
- 4.3 Indication of any immediate medical attention and special treatment need Not required.

#### SECTION 5 Fire-fighting measures

Fire hazards: Combustible

- 5.1 Extinguishing media
  - Suitable extinguishing media: Foam, carbon dioxide, dry chemical powder.

Unsuitable extinguishing media: Water jet.

5.2 Special hazards arising from the <u>mixture</u> or substance Hazardous combustion products:

On burning, carbon monoxide, carbon dioxide, sulphur oxides, calcium oxide, phosphor oxides, various hydrocarbons and soot can be formed.



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

#### Trade name: MOL Transfluid TO-4 SAE 30 gear oil

Version: 6 Latest revision: 25. 09. 2020 Date of issue: 16. 09. 2008

Page: 5/(13)

### 5.3 Advice for fire-fighters

Special protective equipment:

According to the existing fire-fighting regulations. Respiratory protection.

Further information:

Collect contaminated fire fighting water separately. It must not enter the sewage system. Contaminated extinguishing water must be disposed of in accordance with official regulations.

#### SECTION 6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Personal precautions: see Section 8. Danger of slipping on leaked out/spilled product.

#### 6.2 Environmental precautions: Confine spills to prevent material from entering sewers, watercourses, drains and into soil Notify relevant authority.

- 6.3 Methods and material for containment and cleaning up
  - On soil: All kind of ignition sources should be remove. Recover free liquid by pumping. Contain the rest or small quantities with sand, earth or other suitable absorbents. Dispose of according to local regulations.
  - On water: Confine the spillage. Remove from surface by skimming or suitable absorbents. Notify local authorities according to regulations.
- 6.4 Reference to other sections Personal precautions: see section 8. Waste treatment methods: see section 13.

### **SECTION 7** Handling and storage

7.1 Precautions for safe handling

Keep general measures applied for normal operations with lubricants and flammable liquids. Keep away from radiant heat and open flame.

Avoid contact with skin and eyes. Avoid prolonged breathing of oil vapours or mists.

Ensure washing facilities after working hours and before breaks.

Take off contaminated clothing and wash it before reuse.

When using do not eat, drink or smoke. Avoid splashing the product.

Handling temperature: not known



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Transfluid TO-4 SAE 30 gear oil Version: 6

Latest revision: 25. 09. 2020 Date of issue: 16. 09. 2008

Page: 6/(13)

7.2 Conditions for safe storage, including any incompatibilities Storage facilities must comply with regulations for storing of flammable liquids. Store in dry, well ventilated place in original, closed containers. Keep away from radiant heat, open flame and strong oxidizing agents. Storage temperature: max. 40°C

7.3 Specific end use(s) Gear oil.

#### SECTION 8 Exposure controls / personal protection

Engineering control measures: Not required.

8.1 Control parameters:

Mineral oil mist:	TWA: <b>5 mg/m<sup>3</sup></b> ; STEL: 10 mg/m <sup>3</sup> , for oil mist, vapour
	excluded (ACGIH).
	1 1 10000 5006

Method of testing, recommended: NIOSH 5026

8.2 Exposure controls

1	
Personal protection:	
Respiratory protection:	Breathing apparatus not required.
Hand protection:	Oil resistant gloves (EN 374, Breakthrough time 480 min) (e.g.
-	nitrile rubber – minimal thickness 0.33 mm).
	Note: Manufacturer's directions for use and the conditions of
	application should be observed.
Eye protection:	Protective goggles not required.
Skin protection:	Protective clothing (oil resistant).
Other special:	No data.

Environmental exposure controls: Do not discharge into drains/surface waters/groundwater.

#### **SECTION 9** Physical and chemical properties

9.1 Information on basic physical and chemical properties Appearance: Physical state: liquid Colour: brown, clear Odour: characteristic



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name:MOL Transfluid TO-4 SAE 30 gear oilVersion: 6Latest revision: 25. 09. 2020Date of issue: 16. 09. 2008Page: 7/(13)

Change in physical state: Pour point (ISO 3016): typ. -30°C Boiling point (DIN 51356): not available Others: Flash point (COC) (EN ISO 2592): typ. 255°C Ignition point (EN ISO 2592): not available Autoignition temperature: not available Explosive properties: not explosive Oxidizing properties: not oxidize Vapour pressure at 20°C: negligible Density at 15°C (EN ISO 12185):  $0.890 - 0.910 \text{ g/cm}^3$ Solubility in water: practically insoluble in water Solubility in other solvents: gasoline, kerosene, toluene, etc. n-Octanol/water partition coefficient: not available Vapour density: not available Heating value: inf. 38 000 kJ/kg Kinematic viscosity at 40°C (EN ISO 3104): typ. 99.45 mm<sup>2</sup>/s Kinematic viscosity at 100°C (EN ISO 3104): typ. 11.0 mm<sup>2</sup>/s pH: not applicable

9.2 Other information No data available.

#### SECTION 10 Stability and reactivity

10.1	Reactivity:	Dangerous reactivity not known.
10.2	Chemical stability:	No decomposition if stored and handled properly.
10.3	Possibility of hazardous reactions:	Not known.
10.4	Conditions to avoid:	Direct heat or ignition sources.
10.5	Incompatible materials:	Strong oxidizing agents.
10.6	Hazardous decomposition products:	No dangerous decomposition products are formed under normal conditions. Hazardous combustion products: See Section 5.

Γ



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

### Trade name: MOL Transfluid TO-4 SAE 30 gear oil

Version: 6 Latest revision: 25. 09. 2020 Date of issue: 16. 09. 2008

Page: 8/(13)

SEC	SECTION 11 Toxicological information				
11.1	Information on toxicological e Acute toxicity: Oral: LD <sub>50</sub> (rat) Dermal: LD <sub>50</sub> (rabbit	> 2000 mg/kg (based on components)			
	Acute toxicity: irritation Skin: not irritant (	based on components) ed on components)			
	Respiratory or skin sensitisation	on: not sensitising (based on components)			
	Other information, specific eff	ects:			
	Note L: The classification as a carcinogen need not apply according to 1272/2008/EC, because it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346.				
	not known, resp. not mutagen (based on components) not known, resp. not carcinogen (based on components) not known, resp. no reproduction-damaging effect (based on components)				
STOT-single exposure: STOT-repeated exposure: Aspiration hazard:		not classified not classified not classified			
SEC	TION 12 Ecological infor	mation			
12.1	Toxicity No Aquatic organisms: Soil organisms: Plants:	data for the product.			
12.2	Persistence and degradability Biodegradability:	No data available. No data available.			
12.3	Bioaccumulative potential	No data available.			



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Transfluid TO-4 SAE 30 gear oil

Version: 6 Latest revision: 25. 09. 2020 Date of issue: 16. 09. 2008

Page: 9/(13)

Mobility Mobility in soil Mobility in water:	Absorbs in soil. Floats on water.
Results of PBT and vPvB assessment	Does not contain PBT and vPvB substances.
Other adverse effects Heavy metal content: PCT, PCB and other chlorinated	None.
hydrocarbons:	None.
Environmental effects:	Harmful to aquatic life with long lasting effects.
Water hazard class (German):	WGK 2 (Classification by AwSV)
	Mobility in soil Mobility in water: Results of PBT and vPvB assessment Other adverse effects Heavy metal content: PCT, PCB and other chlorinated hydrocarbons: Environmental effects:

#### SECTION 13 Disposal considerations

- 13.1 Waste treatment methods
  - Product disposal:

Wastes of the product or used oil should be treated as hazardous waste. Waste Identification Code: 13 02 05\* Mineral-based non-chlorinated engine, gear and lubricating oils.

Disposal must be in compliance with national and local regulations.

Recommended waste treatment method: incineration

Packaging disposal:

Containers with product residue should also be treated as hazardous waste according to national and local disposal regulations.

Waste Identification Code: 15 01 10\*

Packaging containing residues of or contaminated by dangerous substances.

Disposal must be in compliance with national and local regulations.

Wastewater:

Quality of wastewater emitted to natural water must comply with national and local regulations.

Care should be taken in any case to ensure compliance with EC, national and local regulations. It is the responsibility of the user to know all relevant national and local regulations.



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name:MOL Transfluid TO-4 SAE 30 gear oilVersion: 6Latest revision: 25. 09. 2020Date of issue: 16. 09. 2008Page: 10/(13)

#### SECTION 14 Transport information

Land transport: Road/ Railway	ADR/RID:	Not classified.
<ul> <li>14.1 UN number:</li> <li>14.2 UN proper shipping name:</li> <li>14.3 Transport hazard class(es):</li> <li>14.4 Packing group:</li> <li>14.5 Environmental hazards:</li> <li>14.6 Special precautions for user:</li> </ul>		not classified not classified not classified not classified not classified not classified
Waterways: Inland waterways/ Sea transpor Air transport: ICAO / IATA:	t ADN/IMDG:	Not apply to the product. Not apply to the product.

#### SECTION 15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the mixture. This safety data sheet has been prepared according to Regulation (EC) No 1907/2006 (mod.: 2015/830/EU) and to Regulation (EC) 1272/2008.
- 15.2 Chemical safety assessment. Not available.

#### SECTION 16 Other information

The information given in this data sheet is based on our best knowledge at the time of publication. The information is related only to this product and is intended to assist its safe transport, handling and use. The given physical and chemical parameters describe the product only for the purpose of safety requirements and therefore should not be construed as guaranteeing any specific property of the product or as being part of a product specification or any contract.

The manufacturer or supplier shall not take responsibility for any damages from the use other than recommended or other misuse of the product. It is the responsibility of the user to keep regulatory precautions and observe recommendations for safe use of the product.



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Transfluid TO-4 SAE 30 gear oil

Version: 6 Latest revision: 25. 09. 2020 Date of

Date of issue: 16. 09. 2008

Page: 11/(13)

Test result 1272/2008	Source of data presented in this material safety data sheet: Test results of this product 1272/2008/EC regulation, Annex XVII. of REACH Relevant Hungarian and EU regulations			
Classification (CLP)	Classification for mixtures and used evaluation method according to regulation 1272/2008/EC (CLP)			
Eye Irrit. 2 Aquatic Chro	hic 3 H319 calculated method calculated method			
The full text of	f each relevant Hazard classes and cat., H- phrase in Section 3.:			
H314 H318 H360F H400 H410 H411 H413	Causes severe skin burns and eye damage. Causes serious eye damage. May damage fertility. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects. May cause long lasting harmful effects to aquatic life.			
Skin Corr. 1C Eye Dam. 1 Repr. 1B Aquatic Acute Aquatic Chro Aquatic Chro Aquatic Chro	<ul> <li>Serious eye damage/eye irritation Category 1</li> <li>Reproductive toxicity Category 1B</li> <li>Hazardous to the aquatic environment, Acute Category 1</li> <li>Hazardous to the aquatic environment, Chronic Category 1</li> <li>Hazardous to the aquatic environment, Chronic Category 2</li> </ul>			
Legend: ADN ADR ATE BCF BOD Bw C&L C&L CAS	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways European Agreement concerning the International Carriage of Dangerous Goods by Road Acute Toxicity Estimate Bioconcentration Factor Biological Oxygen Demand Body Weight Classification and Labelling Chemical Abstracts Service			



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name:MOL Transfluid TO-4 SAE 30 gear oilVersion: 6Latest revision: 25. 09. 2020Date of issue: 16. 09. 2008Page: 12/(13)

CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic or toxic to Reproduction
COD	Chemical Oxygen Demand
CSA	Chemical Safety Assessment
CSR	Chemical Safety Report
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
ECHA	European Chemicals Agency
Ecx	Effective Concentration x%
Edx	Effective Dose x%
ELINCS	European List of Notified Chemical Substances
ErC50	EC50 in terms of reduction of growth rate;
ES	Exposure Scenario
ESIS	European Chemical Substances Information System
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LCx	Lethal Concentration x%
LDx	Lethal Dose x%
LOAEC	Lowest Observed Adverse Effect Concentration
LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
NOEC	No observed effect concentration
NOEL	No observed effect level
NLP	No-Longer Polymer
NOAEL	No Observed Adverse Effect Level
OECD	Organisation for Economic Cooperation and Development
PBT	Persistent Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SVHC	Substance of Very High Concern
UVCB	substance of unknown or variable composition, complex reaction products or biological
2.05	materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bio-accumulative

**Revision Indicators:** 

Section	Subject of change	Date	Version
3	Composition/information on ingredients	27.06.2013	2
9 1-16	Physical and chemical properties Revision modification according to 453/2010/EC and		
	1272/2008/EC		



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

### Trade name: MOL Transfluid TO-4 SAE 30 gear oil

Version: 6

Latest revision: 25. 09. 2020

Date of issue: 16. 09. 2008

Page: 13/(13)

Revision Indicators:			
Section	Subject of change	Date	Version
3	Composition/information on ingredients	24.11.2014	3
1-16	Other corrections		
1	Details of the supplier of the safety data sheet,	06.10.2015	4
	Responsible for SDS		
3	Composition/information on ingredients		
9	Physical and chemical properties		
1-16	Other corrections, revision modification according to		
	2015/830 /EU		
2	Hazards identification	02.06.2017	5
3	Composition/information on ingredients		
9	Physical and chemical properties		
14	Transport information		
2	Hazards identification	25.09.2020	6
3	Composition/information on ingredients		
9	Physical and chemical properties		
14	Transport information		
1-16	Other corrections		